

Model	Gear	Voltage(V)	Frequency(Hz)	Power(W)	Airflow(m³/h)	Static Pressure(Pa)	Noise(dB)	Primary Filter(%)	Exchange Efficiency Rate(%)		Enthalpy Exchange Rate(%)		N.W(kg)
									Cooling	Heating	Cooling	Heating	
SYQR-1000	H/L	220	50	600/500	1000/800	245/210	48/46	76.1	61/63	60/69	61/65	65/69	66.5
SYQR-1500	H/L	220	50	1100/900	1500/1200	265/230	52/50	76.1	65/66	68/71	64/68	65/71	67
SYQR-2000	H/L	220	50	1400/1200	2000/1700	270/245	55/53	76.1	64/66	65/73	63/68	66/73	83
SYQR-2500	H/L	220	50	1600/1400	2500/2200	285/255	56/53	76.1	64/69	63/76	63/68	62/72	85
SYQR-3000	/	220/380	50	1900	3000	275	57	76.1	65	69	66	69	106.5
SYQR-4000	/	220/380	50	2200	4000	305	58	76.1	63	71	64	70	107.5
SYQR-5000	/	380	50	3000	5000	320	60	76.1	67	74	60	68	164
SYQR-6000	/	380	50	3300	6000	345	62	76.1	70	77	63	70	195
SYQR-8000	/	380	50	4400	8000	370	65	76.1	71	75	67	72	284