

Model	YDA-870EB	YDA-890EB	YDA-8138EB	YDA-8158EB
Humidity Setting Range	10% ~ 99%RH	10% ~ 99%RH	10% ~ 99%RH	10%~99%RH
Humidity Control Accuracy	±3%RH	±3%RH	±3%RH	±3%RH
Voltage(V-Hz)	220V*50Hz	220V~50Hz	220V*50Hz	220V~50Hz
Dehumidification Capacity(27°C/60%RH)	1.75kg/h	1.9kg/h	2.45kg/h	3.75kg/h
Dehumidification Capacity(30°C/80%RH)	70L/D	90L/D	110L/D	158L/D
Dehumidification Capacity(35°C/90%RH)	90L/D	115L/D	138L/D	180L/D
Power(27°C/60%RH)	830W	860W	1000W	1550W
High - temperature Power(30°C/80%RH)	950W	1050W	1300W	1900W
Max Power(35°C/90%RH)	1180W	1250W	1550W	2200W
Airflow	350m³/h	550m³/h	650m³/h	900m³/h
Refrigerant	R22	R22	R22	R22
Protection Class Against Electric Shock	Class I	Class I	Class I	Class I
Drainage Mode	Water Pipe Drainage	Water Pipe Drainage	Water Pipe Drainage	Water Pipe Drainage
Dimensions (Length x Width x Height)	480*365*885mm	480*435*950mm	480*435*950mm	550*435*1080mm
Weight	40Kg	45Kg	50Kg	68Kg
Application Area	70-90m²	90-110m²	130-150m²	150-180²