

Model	CF6.8DT	CF7.5KT	CF8.8KT	CF10KT	CF12KT
Humidity Setting Range	10%~98%RH	10% ~ 98%RH	10% ~ 98%RH	10% ~ 98%RH	10%~98%RH
Humidity Control Accuracy	±3%RH	±3%RH	±3%RH	±3%RH	±3%RH
Voltage(V-Hz)	220V~50Hz	380V 3N~50Hz	380V 3N~50Hz	380V 3N~50Hz	380V 3N~50Hz
Dehumidification Capacity(27°C/60%RH)	4.0kg/h	4.3kg/h	5.0kg/h	6.0kg/h	6.8kg/h
Dehumidification Capacity(30°C/80%RH)	6.8kg/h	7.5kg/h	8.8kg/h	10kg/h	12kg/h
Dehumidification Capacity(35°C/90%RH)	8.5kg/h	9.0kg/h	11kg/h	13kg/h	14.5kg/h
Power(27°C/60%RH)	1900W	2200W	2500W	2650W	3200W
High - temperature Power(30°C/80%RH)	2300W	2700W	3150W	3400W	4000W
Max Power(35°C/90%RH)	2900W	3300W	3800W	4150W	5000W
Airflow	1200m³/h	1200m³/h	1300m³/h	1800m³/h	2000m³/h
Refrigerant	R22	R22	R22	R22	R410A
Protection Class Against Electric Shock	Class I	Class I	Class I	Class I	Class I
Drainage Mode	Water Pipe Drainage	Water Pipe Drainage	Water Pipe Drainage	Water Pipe Drainage	Water Pipe Drainage
Dimensions (Length x Width x Height)	615*405*1550mm	615*405*1550mm	600*405*1660mm	763*472*1680mm	763*472*1680mm
Weight	84Kg	88Kg	98Kg	128Kg	125Kg
Application Area	200-250m²	200-250m²	200-300m²	300-350m²	300-380m²